



DGNW5POE

5 PORT POE SWITCH

DETAILS

Model	: DGNW5POE
Ports	: 5 (4 POE+ 1Uplink)
Function	: POE
Communication Mode	: Full-Duplex & Half-Duplex
Switch Capacity	: 1.6Gbps.
Transmission Rate	: 10/100Mbps
PoE Budget	: 60Watts
PoE Power Output	: 15.4watts
Ethernet Standards	: IEEE 802.3af

SPECIFICATION

Connector	: 5x 10/100M copper cable RJ45 ports(all ports support MDI/MDIX) 4x PoE ports
Transfer Mode	: Store-And-Forward
Network Medium	: 10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or more UTP (≤100 meter)
Data transmission distance	: 100m
Bandwidth	: 1.6Gbps (non-blocking)
Network Latency	: maximum delay less than 20 microseconds
Packet Buffer Memory	: 768KB
Forwarding Rate	: 0.74Mpps
Address Database Size	: 1K
MTBF	: 100,000 hours
LEDs System	: power supply
LEDs Every Port	: connecting, PoE working status
Power Maximum PoE power	: 65W
Max PoE power for each port	: 30W(1~4 port)
Power input	: AC: 100 to 240V 50-60Hz 2.3A



www.digiferg.com



admin@digiferg.com